



直杆定位销

— 正公差 —

Order 订货示例 型式 (1Type · 2D) - 3L
RD-KAPC4 - 10



Type	材质	硬度
RD-KAP	SUJ2	58HRC~
RD-KAPC	SUS440C	58HRC~
RD-KAPCSS	SUS304	-



③L1尺寸可能会因外径研磨加工而大于产品目录中的值。


l1	型式		③L															
	1Type	2D																
0.4	RD-KAP	1	6	8	10													
0.6		1.5	6	8	10													
1		2	6	8	10	15	20											
		2.5	6	8	10	15	20	25	30									
		3	6	8	10	15	20	25	30	35	40							
1.5		4	8	10	15	20	25	30	35	40	45	50						
		5	8	10	15	20	25	30	35	40	45	50						
2		6	8	10	15	20	25	30	35	40	45	50	55	60				
2.5		8	10	15	20	25	30	35	40	45	50	55	60	65	70	80		
3		10	15	20	25	30	35	40	45	50	55	60	65	70	80			
3.5		12	20	25	30	35	40	45	50	55	60	70	80					
		13	30	40	50	60	70	80										

l1	型式		③L												
	1Type	2D													
0.4	RD-KAPC	1	5	6	8	10									
0.6		1.5	5	6	8	10									
1		2	5	6	8	10	12	15	20						
		2.5	6	8	10	12	15	20							
		3	6	8	10	12	15	20	25	30	35	40			
1.5		4	8	10	12	15	20	25	30	35	40	50			
		5	8	10	12	15	20	25	30	35	40	50			
2		6	8	10	12	15	20	25	30	35	40	50	60		
2.5		8	10	15	20	25	30	35	40	50	60				
3		10	15	20	25	30	35	40	50	60					
3.5		12	30	35	40	50	60								


l1	型式		③L										
	1Type	2D											
0.4	RD-KAPCSS	1	6	8	10								
0.6		1.5	6	8	10								
1		2	6	8	10	12	15						
		2.5	6	8	10	12	15						
		3	6	8	10	12	15	20					
1.5		4	8	10	12	15	20						
		5	10	12	15	20							
2		6	10	15	20	25	30	40					
		6	10	12	15	20	25	30	40	50	60		

交货期 报价确定

Order 订货示例 型式 (1Type · 2D) - 3L
RD-KAPCM4 - 12
RD-KAPV2 - 6




Type	材质	硬度
RD-KAPCM	SUS440C	58HRC~
RD-KAPCSM	SUS304	-




C	型式		③L										
	1Type	2D											
0.3 以下	RD-KAPCM	2	6	8	10	12	15						
		3	10	12	15	20							
		4	10	12	15	20							
0.5	RD-KAPCM	5	10	12	15	20							
		6	10	12	15	20	25						

C	型式		③L										
	1Type	2D											
0.3 以下	RD-KAPCSM	2	6	8	10	12	15						
		3	10	12	15	20							
		4	10	12	15	20							
0.5	RD-KAPCSM	5	10	12	15	20							
		6	10	12	15	20	25						



Type	材质	硬度
RD-KAPV	SUJ2	58HRC~
RD-KAPVC	SUS440C	58HRC~



④恒温室内测得数据。
⑤L1、L2尺寸可能会因外径研磨加工而大于产品目录中的值。

l1	l2	型式		③L										
		1Type	2D											
1	0.2	RD-KAPV	2	6	8	10								
			3	8	10	15	20	25	30					
1.5	0.5		4	10	15	20	25	30						
			5	10	15	20	25	30						
2	6		10	15	20	25	30							
2.5	0.5		8	20	30	40								
			10	30	40	50	60							

l1	l2	型式		③L											
		1Type	2D												
0.4	0.1	RD-KAPVC	1	5	6	8	10								
			1.5	5	6	8	10								
1	0.2		2	5	6	8	10								
			3	6	8	10	15	20	25	30					
			4	8	10	15	20	25	30						
1.5	0.5		5	10	15	20	25	30							
			6	10	15	20	25	30							
2	10		15	20	25	30									
2.5	0.5		8	20	30	40									
			10	30	40	50	60								

交货期 报价确定

磁铁 小零件

磁铁 小零件